

Announcements

Thursday Extra 4:00 in CS Commons/Science 3821

Topic: Lisong Xu, University of Nebraska, Lincoln
Internet bandwidth allocation

Office hours:

Back to normal for the rest of this week

Mentor sessions Sun, Thurs. 8-9 (pm) Commons

Supplemental Problem 2 due Friday

Testing

Clicker Questions

Random number generation

Clicker Questions

Write a function that returns the largest and the smallest of three numbers:

Consider two approaches to solve this problem (distributed separated).

Which code is correct?

- A. Both Approach 1 and Approach 2
- B. Approach 1, but not Approach 2
- C. Approach 2, but not Approach 1
- D. Neither Approach 1 nor Approach 2

Suppose a program is supposed to

- read 10 integers
- find and print the largest
- print the numbers in reverse order

How to identify appropriate tests:

- base tests on statement of problem (black box testing)
- look at code (white box testing)

Black box testing: is the following adequate?

- test with largest in first position (e.g., 9, 8, ..., 0)
- test with largest in second position (e.g., 8, 9, 7, 6,..., 0)
- ... (e.g., put 9 in i th position, with 8, ..., 0 elsewhere)
- test with largest in 10th position (e.g. 8, 7, 6, ... , 0, 9)

A. Adequate

B. Need a couple tests for each position

C. Need to randomize 0, ..., 9

D. Use non-consecutive numbers, with repeats (e.g., 3, 1, 4, 1, ...

E. Need something else (what?)

Consider the following code segments for generating 10 random numbers:

Approach 1:

```
for (int i = 0; i < 10; i++)  
    printf ("%d", rand ());
```

Approach 2:

```
srand (time ((time_t *) 0) );  
for (int i = 0; i < 10; i++)  
    printf ("%d", rand ());
```

Approach 3:

```
for (int i = 0; i < 10; i++)  
{  
    srand (time ((time_t *) 0) );  
    printf ("%d", rand ());  
}
```

Ques. 1: Which print a list of pseudo-random numbers?

Ques. 2: Which print a different list of numbers with each run?

- A. 1 only
- B. 2 only
- C. 3 only
- D. 1 and 2
- E. some other combination