

Announcements

Thursday Extras, Usual schedule

Refreshments: CS Commons @ 4:00; Talk: Science 3821 @ 4:15

No Thursday Extra this week

161 issues: audio, image display

If you are eligible to vote,

be sure to vote—either at your home district or here

Prof. Trish (Poli. Sci.) notes Grinnell students engagement in elections is far below national averages!

Pre-registration suggestions

CSC 207: completes sequence of multiple views of prob. sol.

CSC 213: operating systems—builds on CSC 161

CSC/MAT 208: Discrete Structures— math essential for later CS
(if not taking MAT 218, Discrete Bridges to Adv Mathematics)

CS Major notes

Talk to any CS faculty member (e.g., me), if you have questions about the CS major (e.g., courses, schedule, options, study abroad, etc.)

Since staffing still evolving for CS,

second-year students cannot declare CS major until spring semester

2-dimensional arrays

questions

clicker questions

What is printed by this code?

```
char table[3][4] =  
    { {'a', 'b', 'c', 'd'},  
      {'e', 'f', 'g', 'h'},  
      {'i', 'j', 'k', 'l'} };  
  
printf("%c",table[1][2]);
```

A. b

B. e

C. g

D. j

E. k

```
char table[3][4] =  
    { {'a', 'b', 'c', 'd'},  
      {'e', 'f', 'g', 'h'},  
      {'i', 'j', 'k', 'l'} };
```

Address	Value
table	a
table+1	b
table+2	c
table+3	d
table+4	e
table+5	f
table+6	g
table+7	h
table+8	i
table+9	j
table+10	k
table+11	l
table+12	???
table+13	???
table+14	???
15	???

Which of the following declarations are valid

A. 1, 2, and 3

B. only 1

C. only 2

D. only 3

E. some combination of two

```
1. char table[ ][4] =  
    { {'a', 'b', 'c', 'd'},  
      {'e', 'f', 'g', 'h'},  
      {'i', 'j', 'k', 'l'} };
```

```
2. char table[3][ ] =  
    { {'a', 'b', 'c', 'd'},  
      {'e', 'f', 'g', 'h'},  
      {'i', 'j', 'k', 'l'} };
```

```
3. char table[ ][ ] =  
    { {'a', 'b', 'c', 'd'},  
      {'e', 'f', 'g', 'h'},  
      {'i', 'j', 'k', 'l'} };
```

Which of the following declarations are valid

- A. 1, 2, and 3
- B. only 1
- C. only 2
- D. 1 and 3
- E. 2 + one other

1. `char table[ ][7] =`
 `{ {'a', 'b', 'c', 'd'},`
 `{'e', 'f', 'g', 'h'},`
 `{'i', 'j', 'k', 'l'} };`

2. `char table[4][2] =`
 `{ {'a', 'b', 'c', 'd'},`
 `{'e', 'f', 'g', 'h'},`
 `{'i', 'j', 'k', 'l'} };`

3. `char table[4][7] =`
 `{ {'a', 'b', 'c', 'd'},`
 `{'e', 'f', 'g', 'h'},`
 `{'i', 'j', 'k', 'l'} };`

What is printed by this code?

```
char table[3][4] =  
    { {'a', 'b', 'c', 'd'},  
      {'e', 'f', 'g', 'h'},  
      {'i', 'j', 'k', 'l'} };  
  
printf("%c", *(table+6));
```

- A. f
- B. j
- C. g
- D. Compiler error
- E. Segmentation fault

What is printed by this code?

```
char table[3][4] =  
    { {'a', 'b', 'c', 'd'},  
      {'e', 'f', 'g', 'h'},  
      {'i', 'j', 'k', 'l'} };
```

```
printf("%c",table[1][6]);
```

1. b
2. e
3. g
4. j
5. k
6. Compiler error
7. Run-time error