

Announcements

Thursday Extra

This week: Research students working
with Prof. Vostinar

Supplemental Problem 4

Testing

Bash terminal window

Redirected input

More practice with Linked Lists

Questions

Discuss lab code for templates

Clicker questions

What is printed by the following code, assuming D designates the null list:

```
struct node * ptr = D;  
printf ( "( " );  
while (ptr != NULL)  
{ printf ( " %d", ptr->data);  
  ptr = (*ptr).next;  
}  
printf ( " )\n" );
```

A. ()

B. (
)

C. compile
error

D. possible run-time error

E. something else

Assume B in main points to the first node in the following list:



What happens when main calls proc (B)

```
int proc (struct node * ptr) {  
    int value = 0;  
    while (ptr != NULL)  
        { value += (*ptr).data);  
          ptr = ptr->next);  
        }  
}
```

- A. 20 returned
- B. 26 returned
- C. 28 returned
- D. 28 printed
- E. something else

Assume B in main points to the first node in the following list:



What happens when main calls `proc (B)`

```
int proc (struct node * ptr) {  
    int value = 0;  
    while ((*ptr).next != NULL)  
        { value += (*ptr).data;  
          ptr = ptr->next;  
        }  
}
```

- A. 20 returned
- B. 28 returned
- C. 20 printed
- D. 28 printed
- E. something else

Assume B in main points to the first node in the following list:



What happens when main calls `proc (B)`

```
int proc (struct node * ptr) {  
    int value = 0;  
    if ((*ptr).next != NULL)  
        { value += (*ptr).data);  
          proc (ptr->next);  
        }  
}
```

- A. 20 returned
- B. 26 returned
- C. 28 returned
- D. 28 printed
- E. something else

Assume B in main points to the first node in the following list:



What happens when main calls `proc (B)`

```
void proc (struct node * ptr)
{
    if (ptr != NULL)
    {
        proc (ptr->next);
        printf (" %d", ptr->data);
    }
}
```

- A. 2
- B. 2 7 1 8 2 8
- C. 8 2 8 1 7 2
- D. 8
- E. something else