

Announcements

Thursday Extras: Thursdays (usually) at 4:00 in CS Commons
this week: ??? (watch for email, if talk forthcoming)

Mentor sessions, Tues. 6-7 (pm) CS Commons

CS Study Break, Tues. 8-9 (pm) CS Commons

Slides through today uploaded to course Web (in-class slides)

Office hours this week: Wednesday, Thursday, Friday canceled

Reminder: Robot Action Project due Wednesday at start of class

- signed Academic Honesty statement required
- both paper and electronic copies needed
- for testing with a robot, no output is generated, but you can describe what tests were run and how the robot reacted

Class format adjusted this week

Class meets as usual

Monday normal opening/clickers, lab

Wednesday: normal quiz, relatively more with clickers

Friday: all lab; I'll be out of town; mentors will be helping

Office hours this week: Mon. (1:30-3:00) and Tues. (2:30-4:00) only

Run-time Stack

Questions, Example

Run-time Stack

Notes

- C allows/requires you to work at a level that is close to the hardware
 - provides substantial control of processing
 - basic C principle: programmer knows what to do so little checking—if programmer wants to do something, the programmer must know best!
 - new perspectives for [almost] all in class
 - likely will seem unintuitive for awhile—courage, it gets better over time (e.g., a few class sessions)
- With this class session, we start simply
- May be tempted to skip over details at first
 - avoid this temptation, as later work builds on this!

Consider storage of data in [main] memory for the following program

```
#include <stdio.h>
```

```
int a = -2;
```

```
int b = -13;
```

```
int func (int a, int b)
```

```
{ int c = 2*a + 3*b;
```

```
  printf ("func: a: %6d; b: %6d; c: %6d\n", a, b, c);
```

```
  return c - 7;
```

```
}
```

```
void proc (int c)
```

```
{ int d = func (c, 3);
```

```
  printf ("proc: a: %6d; b: %6d; c: %6d; d: %6d\n", a, b, c, d);
```

```
}
```

```
int main ()
```

```
{ int a = 3;
```

```
  int b = 5;
```

```
  int c, d;
```

```
  printf ("main1: a: %6d; b: %6d; c: %6d; d: %6d\n", a, b, c, d);
```

```
  d = func (b, a);
```

```
  printf ("main2: a: %6d; b: %6d; c: %6d; d: %6d\n", a, b, c, d);
```

```
  proc(a);
```

```
  printf ("main3: a: %6d; b: %6d; c: %6d; d: %6d\n", a, b, c, d);
```

```
}
```