

Quiz

Announcements

Thursday Extras: 4:00 in CS Commons; 4:15 talk in Science 3821

Office hours:

canceled for rest of this week (Wed.-Fri.)

available Sunday 2:00 pm - 4:00 pm

Mentor sessions Tues. 6-7 and 7-8 (pm) Commons

Friday's class devoted to lab time

Functions, address parameters, run-time stack

Questions?

Today's lab on addr. param, run-time stack due next Wed.

Arrays

Questions?

Clicker Questions

Consider the program

```
#include <stdio.h>

int main ()
{ int i;
  int arr[5];
  for (i = 0; i < 5; i++)
      scanf ("%d", &arr[i]);
  for (i = -4; i < 9; i++)
      printf (" %d", arr[i]);
  printf ("\n");
  return 0;
}
```

Suppose the user enters 3 1 4 1 5 on one line, what output is possible?

A. program does not compile, OR

program compiles, but generates a run-time error

B. program runs, but waits for more input on another line

C. 0 0 0 0 3 1 4 1 5 0 0 0 0

D. 0 1 -2 0 3 1 4 1 5 32767 636922497 -335510587 1401318264

E. both C and D

Arrays and Memory

Consider the program.

Suppose the user enters 3 1 4 1 5

```
#include <stdio.h>

int main ()
{ int i;
  int arr[5];
  for (i = 0; i < 5; i++)
    scanf ("%d", &arr[i]);
  for (i = -4; i < 9; i++)
    printf (" %d", arr[i]);
  printf ("\n");
  return 0;
}
```

	-4	0
	-3	1
i	-2	-2
	-1	0
arr	0	3
	1	1
	2	4
	3	1
	4	5
	5	32767
	6	636922497
	7	-335510587
	8	1401318264

What is printed by the following program?

```
#include <stdio.h>

void proc (int arr[])
{
    arr[2] = -5;
}

int main()
{
    int nums[5] = {1,2,3};
    proc(nums);
    printf("%d", nums[2]);
    return 0;
}
```

- A. Does not compile
- B. Crashes when run
- C. 2
- D. 3
- E. -5