

Announcements

Thursday Extras: CS Commons on Thursdays @ 4:00 pm
this week: Off-Campus Study for CS Majors: Why, How, Where?

Office hours:

Wednesday: 1:00-3:00 pm

Thursday: 1:00-3:00 pm

Friday: canceled

Sunday: 2:00-4:00 pm

Reminder: Supplemental Problem 2 due on Monday, but
no penalty if submitted by 5:00 pm on Tuesday

Today: in class: characters, strings, scanf

Friday: in class: Uninterpretable Dance Project

Reflections on for and while statements

Characters, strings, scanf

questions

clicker questions

Consider the following code segments for generating 10 random numbers:

Approach 1:

```
for (int i = 0; i < 10; i++)  
    printf ("%d", rand ());
```

Approach 2:

```
srand (time ((time_t *) 0) );  
for (int i = 0; i < 10; i++)  
    printf ("%d", rand ());
```

Approach 3:

```
for (int i = 0; i < 10; i++)  
{  
    srand (time ((time_t *) 0) );  
    printf ("%d", rand ());  
}
```

Ques. 1: Which print a list of pseudo-random numbers?

Ques. 2: Which print a different list of numbers with each run?

- A. 1 only
- B. 2 only
- C. 3 only
- D. 1 and 2
- E. some other combination